



SOLARO 3320 O E AW

Product information

Main Function	Ultimate solar protection
System	Rolling, Sliding
Material composition	85% Polyolefin, 15% Aluminium
Pattern	1 aluminum, 2 open
Flame retardant	No
Warranty	Warranty five (5) years under all types of greenhouse covering and three (3) years with outdoor use, see Svensson's limited warranty for all terms, conditions, and exclusions in writing.

Mechanical properties	Value	Unit	Test methods
Weight	155	g/m ²	
Thickness	1.3	mm	
Width of strips	4.8	mm	
Tensile strength (length/width)*	445/320	N/5cm	ISO 13934-1
Elongation (length/width)*	45/40	%	ISO 13934-1

Physical properties	Value	Unit	Test methods
Shading level in direct light, PAR**	33	%	According to Svensson
Shading level in diffused light, PAR**	44	%	According to Svensson
UV light transmission***	62	%	Integrated sphere
Shading efficiency	1		According to Svensson
Energy saving	20	%	

* Width 50 mm

** PAR = 400 - 700 nm, accuracy +/- 1%

*** UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, Svensson does not accept any liability in respect of its accuracy. Further information concerning the product and its installation may be obtained from Svensson and its authorized distributors. Svensson's products and name are protected by patent and other intellectual property rights. Products marked FR are flame retardant. No other products delivered by Svensson are flame retardant. AB Ludvig Svensson is an ISO 14001/90001 certified company.