



## SOLARO 7830 O R FR AG

### Product information

Main Function	Ultimate solar protection
System	Rolling
Material composition	64% Polyolefin, 36% Aluminium
Pattern	3 aluminium, 1 open
Flame retardant	Yes
Warranty	Warranty five (5) years under all types of greenhouse covering, see Svensson's limited warranty for all terms, conditions, and exclusions in writing.

Mechanical properties	Value	Unit	Test methods
Weight	180	g/m <sup>2</sup>	
Width of strips	4.6	mm	

  

Physical properties	Value	Unit	Test methods
Shading level in direct light, PAR**	78	%	According to Svensson
Shading level in diffused light, PAR**	80	%	According to Svensson
Energy saving	30	%	

\* Width 50 mm

\*\* PAR = 400 - 700 nm, accuracy +/- 1%

\*\*\* UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, Svensson does not accept any liability in respect of its accuracy. Further information concerning the product and its installation may be obtained from Svensson and its authorized distributors. Svensson's products and name are protected by patent and other intellectual property rights. Products marked FR are flame retardant. No other products delivered by Svensson are flame retardant. AB Ludvig Svensson is an ISO 14001/90001 certified company.