



## SOLARWOVEN GREEN

### Product information

Main Function	Protection against sun radiation, frost, hail, downpour and wind
System	Rolling
Material composition	100% Polyolefine
Pattern	Plastic full
Flame retardant	No
Warranty	Please contact your Svensson representative for warranty information.

Mechanical properties	Value	Unit	Test methods
Weight	215	g/m <sup>2</sup>	
Thickness	0.3	mm	
Tensile strength (length/width)*	1000/433	N/5cm	ISO 13934-1
Elongation (length/width)*	19/10	%	ISO 13934-1

  

Physical properties	Value	Unit	Test methods
Shading level in direct light, PAR**	44	%	According to Svensson
Shading level in diffused light, PAR**	46	%	According to Svensson
UV light transmission***	3	%	Integrated sphere
Energy saving	40	%	According to Svensson

\* Width 50 mm

\*\* PAR = 400 - 700 nm, accuracy +/- 1%

\*\*\* UV-light = 300 - 400 nm

This product image is for illustrative purposes only and may vary in appearance and design from the delivered product. Although the information in this data sheet has been composed with care, Svensson does not accept any liability in respect of its accuracy. Further information concerning the product and its installation may be obtained from Svensson and its authorized distributors. Svensson's products and name are protected by patent and other intellectual property rights. Products marked FR are flame retardant. No other products delivered by Svensson are flame retardant. AB Ludvig Svensson is an ISO 14001/90001 certified company.